6061 Aluminium Sheet

Smiths Advanced Metals

Rev: SAM/datasheets/aluminium/6061-sheet/feb-2022

Heat-treatable aluminium sheet

Medium to high strength alloy

6061 is a medium to high strength aluminium alloy with magnesium and silicon as the main alloying elements. We stock 6061 aluminium in sheet form in 0, T4, T42, T6 tempers.

6061 aluminium offers various attractive characteristics making the alloy an extremely versatile engineering material for commercial applications. Features include medium fatigue strength and very good corrosion resistance. The alloy also benefits from good weldability, although overall strength is reduced in the welding zone. Cold formability is also good.

6061 aluminium sheet finds typical use in applications where a combination of improved corrosion resistance and strength is a requirement.

We stock and supply 6061 aluminium sheets in a wide range of thicknesses and tempers, including 0, T4, T42, T6. We also offer in-house processing services where we guillotine your aluminium sheets to your size requirements.

Grades / Specifications

- AMS 4025
- AMS 4027
- AMSQQA250/11
- ASTM B209
- BS EN 573, BS EN 485





Key Applications

- Aerospace parts
- Military components
- Structural applications
- Pylons and towers

Chemical Composition (weight %)											
	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Others (ea)	Others (total)	Al
min.	0.40		0.15		0.80	0.04					Rem
max.	0.80	0.70	0.40	0.15	1.20	0.35	0.25	0.15	0.05	0.15	

Mechanical Properties (min. values, 1.5 - 3mm thick sheet									
Temper	MPa _{Rm}	MPa R _{p0,2}	Elongation A50 mm	Hardness HBW Typical					
T4	205	110	14	58					
T42	205	95	14	57					
Т6	290	240	7	88					

Physical Properties							
T4	T6						
2.70	2.70						
580 - 650	580 - 650						
39.6	39.6						
43	40						
70	70						
	T4 2.70 580 - 650 39.6 43 70						

info@smithsadvanced.com

Properties as per BS EN 485-2

www.**smithsadvanced**.com



Stratton Business Park, London Road, Biggleswade, Bedfordshire SG18 8QB

Tel: +44 (0) 1767 604710



All information in our data sheet is based on approximate testing and is stated to the best of our knowledge and belief. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of trading. © Smiths Advanced Metals 2023